



FULL LEVEL BEARING  
SHALL BE PROVIDED  
UNDER EACH FOOT  
PAD AREA

NOTE: ALL MEASUREMENTS ARE OD TO OD OF FOOTPAD.  
ALL GIVEN DIMENSIONS ARE WITHIN ±1/8".

"DRAWING IS FOR REFERENCE PURPOSES ONLY AND NOT TO BE USED FOR CONSTRUCTION"

<b>FOR APPROVAL BY</b>		<b>DATE</b>
Tower Tech Design Team		
<b>REVISIONS</b>		
<b>NO.</b>	<b>DATE</b>	<b>REVISION</b>
<b>DATE:</b>		<b>25 APR 19</b>
<b>DRAWING#:</b>		<b>XL-12-3</b>
<b>PROJECT#:</b>		
<b>CUST PO#:</b>		
<b>DRAWN BY:</b>		<b>RFB</b>
<b>CHECKED BY:</b>		
<b>FOOTPRINT &amp; ANCHOR PAD LAYOUT</b>		<b>3</b>

### 1-Unit Installation

### TTXL-12 Anchor Pad Layout

Modular  
Fiberglass  
Cooling Tower  
Model # TTXL-1219XX

© 2001 BY TOWER TECH  
ALL RIGHTS RESERVED



## TOWER TECH

TELEPHONE: (405) 979-2100  
FAX: (405) 979-2131  
E-MAIL: [cad@towertechusa.com](mailto:cad@towertechusa.com)  
WEBPAGE: <http://www.towertechusa.com>  
5400 NW 5th  
OKLAHOMA CITY, OKLAHOMA 73127